

**SPECIFICATION SHEET FOR 360° SWIVEL SKIP  
TRACKED DUMPERS**



Tonnage	4 Tonne Swivel	6 Tonne Swivel	7 Tonne Swivel	8 Tonne Swivel	10 Tonne Swivel	12 Tonne Swivel	14 Tonne Swivel
Model No	TDH40S	TDH60S	TDH70S	TDH80S	TDH100S	TDH120S	TDH140S
Full Length (a) mm	3090	4100	4825	5400	6000	5405	6000
Full Width (f) mm	1940	2640	2640	2910	3000	3330	3490
Full Height (b) mm	2640	2430	2775	2870	3000	3185	3000
Machine weight (kg)	2780	6200	8500	10800	16100	15600	16100
Dump Body L (d) mm	1655	2130	2725	2950	3400	3290	3400
Dump Body W (e) mm	1690	2075	2095	2200	2750	2680	2930
Dump Body H mm	340	350	400	380	485	535	750
Ground Clearance (mm)	295	420	500	513	560	685	560
Track Width (mm)	380	500	600	700	800	800	800
Max. Payload (kg)	4000	6000	7000	8000	10000	12000	14000
Cabin	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Engine Make	Komatsu	Isuzu	Komatsu	Isuzu	Isuzu	Komatsu	Isuzu
Engine Model	4D883-3D	A-4BG1T	S6D102E1A	CC-6BG1T	AA-6HK1TC	SAA6D114E	AA-6HK1TC
Fuel Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Fuel Tank cap (litres)	49	100	130	165	300	300	300
Braking	Service	Service	Service	Service	Service	Service	Service
Drive System	HST	HST	HST	HST	HST	HST	HST
Transmission	2 Speed	2 Speed	2 Speed	2 Speed	2 Speed	2 Speed	2 Speed
<b>Performance</b>							
Ground Pressure kg/cm2	0.17	0.24	0.17	0.20	0.26	0.25	0.26
Ground Pressure psi			3.1			3.6	3.6
Speed 1st Gear km/h	0-5.6	0-6.0	0-6.0	0-7.0	0-7.0	0-4.5	0-7.0
Speed 2nd Gear km/h	0-8.3	0-11.0	0-8.5	0-10	0-10	0-10	0-10
Gradient Ability (deg)	57	57	57	58	58		
Turning radius (m)	2.2	2.2	3.05	2.95	3.55	2.8	2.8

Although every care has been taken, Tracked Dumper accepts no responsibility for any discrepancies in these figures. Please note our machines are fitted with either rubber or steel tracks. Please call +44 (0)1328 830060 for further details.

**SPECIFICATION SHEET FOR 360° SWIVEL SKIP  
TRACKED DUMPERS**



Although every care has been taken, Tracked Dumper accepts no responsibility for any discrepancies in these figures. Please note our machines are fitted with either rubber or steel tracks. Please call +44 (0)1328 830060 for further details.